

a wide range of units both for perimeter and rack cooling from 4,5 to 235 kW

## Rack cooling solutions

### CCD Cooling Door



**Chilled water cooling door unit,**  
from 26,6 to 39 kW

Suitable for 600mm wide racks.

### CRC Rack Cooler



**Rack cooling solutions for high density rack management,**  
from 10 to 75 kW

- CRCX:** Direct expansion version
- CRCC:** Chilled water version
- CRCD:** Dual Fluid version
- CRCF:** Free cooling version

## Remote condensers



**Remote condenser with axial fans**

**BRE** 7 - 187 kW  
**i-BRE** 13,4-187 kW



**Remote condenser with centrifugal fans**

**BREC M1D-M4F\_B**  
16,1-108 kW

## Dry coolers



**Dry Cooler with axial-type fan**

**BDC** 8-210 kW  
**i-BDC** 14-210 kW

## Climaveneta infrastructures



**CV RACK**  
High quality cabinets for protecting and housing servers



**CV AISLE CONTAINMENT**  
Aisle Containment solution for high density applications

## Management and control systems

In a policy of 'total communication', the Climaveneta HPAC range presents several interconnection solutions with the latest BMS systems.



**Clima Guard**  
Monitoring and supervision device



**Clima Center**  
Supervision device for monitoring the perimeter ACCURATE air conditioners



**ClimaPRO**  
Chiller plant control and optimisation system